Käpylä Bollard

IP44 E27 GLC RST H450

Universal luminaire

The classic and timeless Käpylä luminaires are a great solution for lighting pathways and plantings in yards and gardens. The glass dome protects the bulb and steers the light both upwards and downwards through the body's steel rings. Install together with a concrete base and a support tube (4107058), or choose a ground support tube (4107104) that can be sunk directly into the ground. To create a harmonious look for your yard, complement the Käpylä bollards with Käpylä wall luminaires.

Käpylä Bollard Outdoor luminaire IP44; IK02; Protection cl. I; LED exchangeable; Ending; 3x2.5mm²; Housing st; Colour st; Cover Glass transparent

Stocked: Yes









IP44 E27 GLC RST H450			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4107070	4107070	1.208	Käpylä Bollard

IP44 E27 GLC RST H450

EC000301 Bollard luminaire

Mounting	
Type of luminaire	Bollard luminaire
Degree of protection (IP)	IP44
Impact strength	IK02
Type of wiring	Ending
Number of poles	3
Conductor cross section (mm²)	2.5 mm²
Connection type	Screwed terminal

Structure	
With base plate	Yes
Lamp type	LED exchangeable
Light source included	No
Suitable for number of lamps	1
Lamp holder	E27
Housing material	Stainless steel
Material quality housing material	Stainless steel 304
Surface protection	Untreated
Housing colour	Stainless steel
Cover material	Glass transparent
Control gear included	No
Exchangeable control gear	No
Energy efficiency class of light source according to EU regulation 2019/2015	Not required

Dimming and control	
With light sensor	No
With movement sensor	No
Constant luminous flux control	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220 V
Nominal voltage (max) (V)	240 V
Type of control gear	Not required
Protection class according to IEC 61140	I
Suitable for lamp power (min) (W)	1 W
Suitable for lamp power (max) (W)	11 W

Photometric data	
Light distributor	Other
Light sharing	Symmetric
Light outlet	Direct/indirect
Beam angle	Open beam
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Measurements	
Width (mm)	221 mm
Height/depth (mm)	450 mm
Length (mm)	221 mm
Diameter (mm)	221 mm