Kartano Bollard

IP44 E27 GLC WH H1150

Universal luminaire

The design of the Kartano Bollard range is reminiscent of old street lanterns. Its classic appearance and materials will stand the test of time. With its ceramic lamp holder and bevelled glass panes, the luminaire is made of high-quality materials that complement its timeless design. With our popular Kartano luminaires, you can build a harmonious lighting solution. Select the bollard- and pole-mounted models that best suit your garden and complement them with wall-mounted Kartano luminaires.

Kartano Bollard Outdoor luminaire No dim; IP44; Protection cl. I; LED exchangeable; Ending; 3x2.5mm²; Housing al; Colour wh; Cover Glass transparent

Stocked: Yes





IP44 E27 GLC WH H1150

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4107197	4107197	2	Kartano Bollard

IP44 E27 GLC WH H1150

EC000062 Street lighting

Mounting	
Mounting method	Other
Degree of protection (IP)	IP44
Luminaire with limited surface temperature, class "D“ in acc. with EN 60598-2-24	No
Type of wiring	Ending
Number of poles	3
Conductor cross section (mm²)	2.5 mm²
Connection type	Screwed terminal

Structure	
Lamp type	LED exchangeable
Light source included	No
Suitable for number of lamps	1
Lamp holder	E27
Housing material	Aluminium
Surface protection	Powder coating
Housing colour	White
Cover material	Glass transparent
Adjustable optics	No
Energy efficiency class of light source according to EU regulation 2019/2015	Not required
With connection cable	Yes

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220 V
Nominal voltage (max) (V)	240 V
Type of control gear	Not required
Protection class according to IEC 61140	I
Suitable for lamp power (min) (W)	1 W
Suitable for lamp power (max) (W)	100 W

Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming DSI	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
Remote control	None
With wireless control	No
Constant luminous flux control	No
With light regulation program control	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Lifetime and capacity	
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	-20 °C
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	35 °C

Measurements	
Width (mm)	225 mm
Height/depth (mm)	1150 mm
Length (mm)	225 mm

AIRAM