# Kartano Pole



## IP44 E27 GLC WH Pole

Universal luminaire

With the Kartano Pole luminaires, you can add a touch of old-world charm to your garden. The classic design and carefully chosen materials, the ceramic lamp holder and bevelled glass panes will stand the test of time. Select the bollard- and pole-mounted models that best suit your garden and house and complement them with wall-mounted Kartano luminaires.

Kartano Pole Outdoor luminaire No dim; IP44; Protection cl. I; LED exchangeable; Ending; 3x2.5mm²; Housing al; Colour wh; Cover Glass transparent

Stocked: Yes




| IP44 E27 GLC WH Pole | | | |
|---|---|---|---|
| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
| 4107199 | 4107199 | 3 | Kartano Pole |

# IP44 E27 GLC WH Pole

EC000062 Street lighting

| Mounting | |
|---|---|
| Mounting method | Other |
| Degree of protection (IP) | IP44 |
| Luminaire with limited surface temperature, class "D“ in acc. with EN 60598-2-24 | No |
| Type of wiring | Ending |
| Number of poles | 3 |
| Conductor cross section (mm²) | 2.5 mm² |
| Connection type | Screwed terminal |

| Structure | |
|---|---|
| Lamp type | LED exchangeable |
| Light source included | No |
| Suitable for number of lamps | 1 |
| Lamp holder | E27 |
| Housing material | Aluminium |
| Surface protection | Powder coating |
| Housing colour | White |
| Cover material | Glass transparent |
| Adjustable optics | No |
| Energy efficiency class of light source according to EU regulation 2019/2015 | Not required |
| With connection cable | Yes |

| Electrotechnical data | |
|---|---|
| Voltage type | AC |
| Nominal voltage (min) (V) | 220 V |
| Nominal voltage (max) (V) | 240 V |
| Type of control gear | Not required |
| Protection class according to IEC 61140 | I |
| Suitable for lamp power (min) (W) | 1 W |
| Suitable for lamp power (max) (W) | 100 W |

| Dimming and control | |
|---|---|
| Dimming 0-10 V | No |
| Dimming 1-10 V | No |
| Dimming DALI | No |
| Dimming DMX | No |
| Dimming DSI | No |
| Dimming potentiometer (integrated) | No |
| Dimming LineSwitch | No |
| Dimming manufacturer's proprietary system | No |
| Dimming mains voltage modulation | No |
| Dimming trailing edge | No |
| Dimming leading edge | No |
| Dimming programmable | No |
| Dimming RF | No |
| Dimming Sine Wave Reduction | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming with push-button | No |
| No dimming function | Yes |
| Remote control | None |
| With wireless control | No |
| Constant luminous flux control | No |
| With light regulation program control | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

| Lifetime and capacity | |
|---|---|
| Rated ambient temperature acc. IEC62722-2-1 (min) (°C) | -20 °C |
| Rated ambient temperature acc. IEC62722-2-1 (max) (°C) | 35 °C |

| Measurements | |
|---|---|
| Width (mm) | 245 mm |
| Height/depth (mm) | 1755 mm |
| Length (mm) | 248 mm |

AIRAM