Kallio

IP44 E27 GLC ANT H900

Universal luminaire

Kallio bollards are ideal for lighting pathways and plantings in the yard. The splash proof body of the upright Kallio light is made of stainless steel. You can choose between two colour and coating options for the body: grey stone coating or powder-painted anthracite grey with a matte surface. The tempered glass dome disperses the light beautifully. Install together with a concrete base and a support tube (4107058), or choose a ground support tube (4107104) that can be sunk directly into the ground.

Kallio Outdoor luminaire IP44; Protection cl. I; LED exchangeable; Ending; 3x2.5mm²; Housing st; Colour ant; Cover Glass transparent

Stocked: Yes







IP44 E27 GLC ANT H900			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4116122	4116122	4.645	Kallio

IP44 E27 GLC ANT H900

EC000301 Bollard luminaire

Mounting	
Type of luminaire	Bollard luminaire
Degree of protection (IP)	IP44
Type of wiring	Ending
Number of poles	3
Conductor cross section (mm²)	2.5 mm²
Connection type	Screwed terminal

Structure	
With base plate	No
Lamp type	LED exchangeable
Light source included	No
Suitable for number of lamps	1
Lamp holder	E27
Housing material	Stainless steel
Material quality housing material	Stainless steel 304
Surface protection	Powder coating
Housing colour	Anthracite
Cover material	Glass transparent
Control gear included	No
Energy efficiency class of light source according to EU regulation 2019/2015	Not required

Dimming and control	
With light sensor	No
With movement sensor	No
Constant luminous flux control	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220 V
Nominal voltage (max) (V)	240 V
Type of control gear	Not required
Protection class according to IEC 61140	I
Suitable for lamp power (min) (W)	1 W
Suitable for lamp power (max) (W)	7.5 W

Photometric data	
Light distributor	Other
Light sharing	Symmetric
Light outlet	Direct
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Measurements	
Width (mm)	140 mm
Height/depth (mm)	900 mm
Length (mm)	104 mm