Kartano Trumpet Pole



IP44 2XE27 PCC BK

Universal luminaire

The Kartano Trumpet Pole is a modern take on an old lantern. As the shape of the lamp is clearly visible through the diffuser, you can adjust the ambience and brightness of your space with the lamp you choose. Build a harmonious lighting solution with Trumpet wall luminaires.

Kartano Trumpet Pole Outdoor luminaire No dim; IP44; Protection cl. I; LED exchangeable; Ending; 3x2.5mm²; Housing al; Colour bk; Cover Plastic, transparent

Stocked: Yes

IP44 2XE27 PCC BK			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4116406	4116406	7.5	Kartano Trumpet Pole

IP44 2XE27 PCC BK

EC000062 Street lighting

Mounting	
Mounting method	Other
Degree of protection (IP)	IP44
Luminaire with limited surface temperature, class "D“ in acc. with EN 60598-2-24	No
Type of wiring	Ending
Number of poles	3
Conductor cross section (mm²)	2.5 mm²
Connection type	Screwed terminal

Structure	
Lamp type	LED exchangeable
Light source included	No
Suitable for number of lamps	2
Lamp holder	E27
Housing material	Aluminium
Surface protection	Powder coating
Housing colour	Black
Cover material	Plastic, transparent
Adjustable optics	No
Energy efficiency class of light source according to EU regulation 2019/2015	Not required
With connection cable	Yes

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220 V
Nominal voltage (max) (V)	240 V
Type of control gear	Not required
Protection class according to IEC 61140	I
Suitable for lamp power (min) (W)	1 W
Suitable for lamp power (max) (W)	100 W

Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming DSI	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
Remote control	None
With wireless control	No
Constant luminous flux control	No
With light regulation program control	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Lifetime and capacity	
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	-20 °C
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	35 °C

Measurements	
Width (mm)	795 mm
Height/depth (mm)	2200 mm
Length (mm)	260 mm

AIRAM