# Sund Double

## IP44 2XGU10 GLC WH Sund D



Surface mnt. univ. luminaire

The elegant Sund Double distributes light downwards and upwards. Thanks to its compact size, Sund offers an ideal solution for a wide range of applications indoors and outdoors. As a light source, you can select a GU10 lamp with a colour temperature, luminous flux and beam of your choice. With narrow-beamed spotlights, you can create vertical lines and highlight your building's architectural features.

Sund Double Surface mnt. univ. luminaire No dim; IP44; IK06; Protection cl. I; LED exchangeable; Ending; 3x2.5mm²; Housing al; Colour wh; Cover Glass transparent

Stocked: Yes

| IP44 2XGU10 GLC WH Sund D | | | |
|---|---|---|---|
| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
| 4118742 | 4118742 | 0.528 | Sund Double |








# IP44 2XGU10 GLC WH Sund D

EC002892 Ceiling / wall luminaire

| Mounting | |
|---|---|
| Suitable for wall mounting | Yes |
| Suitable for suspended mounting | No |
| Suitable for ceiling mounting | No |
| Suitable for recessed mounting | No |
| Suitable for surface mounting | Yes |
| Suitable for light line configuration | No |
| Suitable for clamp-mounting | No |
| Fit for workplace acc. EN 12464-1 | No |
| Degree of protection (IP) | IP44 |
| Degree of protection (IP), rear side | IP44 |
| Degree of protection (IP), front side | IP44 |
| Impact strength | IK06 |
| Luminaire with limited surface temperature, class "D“ in acc. with EN 60598-2-24 | No |
| Suitable for emergency lighting | No |
| Type of wiring | Ending |
| Number of poles | 3 |
| Conductor cross section (mm²) | 2.5 mm² |
| Connection type | Screwed terminal |

| Structure | |
|---|---|
| With mounting material | Yes |
| Lamp type | LED exchangeable |
| Light source included | No |
| Suitable for number of lamps | 2 |
| Lamp holder | GU10 |
| Housing material | Aluminium |
| Housing surface protection | Powder coating |
| Housing colour | White |
| Cover material | Glass transparent |
| Type of grid | None |
| Control gear included | No |
| Exchangeable control gear | No |
| Energy efficiency class of light source according to EU regulation 2019/2015 | Not required |
| Emergency power supply integrated | No |
| With switch | No |
| With air slots | No |
| Filament test according to IEC 60695-2-11 | 650 °C - 30 s |

| Electrotechnical data | |
|---|---|
| Voltage type | AC |
| Nominal voltage (min) (V) | 220 V |
| Nominal voltage (max) (V) | 240 V |
| Type of control gear | Not required |
| Protection class according to IEC 61140 | I |
| Suitable for lamp power (min) (W) | 1 W |
| Suitable for lamp power (max) (W) | 7 W |

| Dimming and control | |
|---|---|
| Dimming 0-10 V | No |
| Dimming 1-10 V | No |
| Dimming DALI | No |
| Dimming DALI-2 | No |
| Dimming DMX | No |
| Dimming DSI | No |
| Dimming LineSwitch | No |
| Dimming manufacturer's proprietary system | No |
| Dimming mains voltage modulation | No |
| Dimming trailing edge | No |
| Dimming leading edge | No |
| Dimming programmable | No |
| Dimming potentiometer (integrated) | No |
| Dimming RF | No |
| Dimming Sine Wave Reduction | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming with push-button | No |
| No dimming function | Yes |
| With movement sensor | No |
| With light sensor | No |
| Constant luminous flux control | No |
| Bluetooth operated | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

| Photometric data | |
|---|---|
| Light distributor | None |
| Light sharing | Symmetric |
| Light outlet | Direct/indirect |
| Colour temperature switchable | No |
| Lumen setting adjustable | No |
| Beam angle adjustable | No |

| Lifetime and capacity | |
|---|---|
| Rated ambient temperature acc. IEC62722-2-1 (min) (°C) | -20 °C |
| Rated ambient temperature acc. IEC62722-2-1 (max) (°C) | 25 °C |

| Measurements | |
|---|---|
| Width (mm) | 68 mm |
| Height/depth (mm) | 150 mm |
| Length (mm) | 93 mm |