# Target M

## IP20 21W/930 2580lm 36D WH





Spotlight

Target M offers an ideal spotlight solution for retail premises. This luminaire offers high-quality illumination and excellent colour rendering properties. Its Premium White feature is specifically designed for in-store spot and accent lighting. The feature enhances colour contrasts, emphasising white colour tones. The luminaire is equipped with an almost inconspicuous ballast that is integrated into a three-phase rail. Thanks to its versatility, this luminaire offers a wide range of lighting options for retail spaces as it is easy to move and adjust. Suitable applications include fashion and clothing retail premises, museums and other public spaces.

Target M Spotlight 21W 3000K 2580lm Beam angle Medium beam 20-40°; No dim; IP20; IK02; Protection cl. II; L70B50 100000h; LED not exchangeable; Lamp included; CRI>90; SDCM3; Ending; 3x2.5mm²; Housing al; Colour wh; Cover Plastic, transparent; C16 max. 61

Stocked: No




| IP20 21W/930 2580lm 36D WH | | | |
|---|---|---|---|
| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
| 4146584 | 4146584 | 0.7 | Target M |

# IP20 21W/930 2580lm 36D WH

EC001744 Downlight / spot luminaire / floodlight

| Mounting | |
|---|---|
| Suitable for surface mounting | No |
| Suitable for recessed mounting | No |
| Suitable for wall mounting | Yes |
| Suitable for suspended mounting | No |
| Suitable for ceiling mounting | Yes |
| Suitable for traverse mounting | No |
| Suitable for pedestal/floor mounting | No |
| Suitable for light-track mounting | Yes |
| Suitable for clamp-mounting | No |
| Suitable for low voltage cable system | No |
| Degree of protection (IP) | IP20 |
| Degree of protection (IP), rear side | IP20 |
| Degree of protection (IP), front side | IP20 |
| Impact strength | IK02 |
| Emergency function monitoring system | None |
| Type of wiring | Ending |
| Number of poles | 3 |
| Conductor cross section (mm²) | 2.5 mm² |
| Connectable conductor cross section (min) (mm²) | 1.5 mm² |
| Connectable conductor cross section (max) (mm²) | 2.5 mm² |
| Connection type | Busbar adapter |
| Luminaire with limited surface temperature, class "D“ in acc. with EN 60598-2-24 | No |
| Max. number of luminaires per miniature circuit breaker B16 | 50 |
| Max. number of luminaires per miniature circuit breaker C16 | 85 |
| Fit for workplace acc. EN 12464-1 | No |
| Luminaire may be covered with thermally insulating material | - |

| Structure | |
|---|---|
| Adjustability | Rotating and swivelling |
| Lamp type | LED not exchangeable |
| Light source included | Yes |
| Suitable for number of lamps | 1 |
| Lamp holder | Other |
| Housing material | Aluminium |
| Surface protection | Powder coating |
| Housing colour | White |
| Cover material | Plastic, transparent |
| Surface brushed | No |
| Control gear included | Yes |
| Exchangeable control gear | Yes |
| Reflector | High-gloss |
| Reflector colour | Silver |
| Energy efficiency class of light source according to EU regulation 2019/2015 | E |
| Containing product according to 2019/2020/EU | Yes |
| Emergency power supply system | None |
| Emergency power supply integrated | No |
| Filament test according to IEC 60695-2-11 | 650 °C - 30 s |

AIRAM

| Dimming and control | |
|---|---|
| With movement sensor | No |
| With presence indicator | No |
| With light sensor | No |
| Dimmable | No |
| Dimming 0-10 V | No |
| Dimming 1-10 V | No |
| Dimming DALI-2 | No |
| Dimming DALI | No |
| Dimming DMX | No |
| Dimming DSI | No |
| Dimming potentiometer (integrated) | No |
| Dimming LineSwitch | No |
| Dimming manufacturer's proprietary system | No |
| Dimming mains voltage modulation | No |
| Dimming trailing edge | No |
| Dimming leading edge | No |
| Dimming programmable | No |
| Dimming RF | No |
| Dimming Sine Wave Reduction | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming with push-button | No |
| No dimming function | Yes |
| Constant luminous flux control | No |
| IFTTT support available | No |
| Compatible with Apple HomeKit | No |
| Bluetooth operated | No |
| Compatible with Google Assistant | No |
| Compatible with Casambi | No |
| Compatible with Amazon Alexa | No |

| Electrotechnical data | |
|---|---|
| Voltage type | AC |
| Nominal voltage (min) (V) | 220 V |
| Nominal voltage (max) (V) | 240 V |
| Nominal current (min) (mA) | 550 mA |
| Nominal current (max) (mA) | 550 mA |
| Type of control gear | LED operating device current-controlled |
| Total harmonic distortion (THD) (%) | 15 % |
| Total harmonic distortion | 15 THD |
| Protection class according to IEC 61140 | II |
| Suitable for lamp power (min) (W) | 21 W |
| Suitable for lamp power (max) (W) | 21 W |
| Maximum system power (W) | 21 W |
| Luminaire efficacy (min) (lm/W) | 123 lm/W |
| Luminaire efficacy (max) (lm/W) | 123 lm/W |
| Power factor | 0.95 |
| Luminaire efficacy (lm/W) | 123 lm/W |

| Photometric data | |
|---|---|
| Light distributor | Reflector |
| Light sharing | Symmetric |
| Beam angle | Medium beam 20-40° |
| Light outlet | Direct |
| Colour of light (alphanumeric) | White |
| Colour temperature (min) (K) | 3000 K |
| Colour temperature (max) (K) | 3000 K |
| Colour temperature switchable | No |
| Colour rendering index (CRI/Ra) | 90-100 |
| Luminous flux (min) (lm) | 2580 lm |
| Luminous flux (max) (lm) | 2580 lm |
| Effective luminous flux (lm) | 2580 lm |
| Rated luminous flux according to IEC 62722-2- 1 (min) (lm) | 2580 lm |
| Rated luminous flux according to IEC 62722-2- 1 (max) (lm) | 2580 lm |
| Lumen setting adjustable | No |
| Flickering value Pst LM | 1 |
| Beam angle adjustable | No |
| Stroboscope effect value SVM | 0.4 |
| Photobiological safety according to EN 62471 | RG1 |
| Colour consistency (McAdam ellipse) | SDCM3 |

| Lifetime and capacity | |
|---|---|
| Rated life time L70/B50 at 25 °C (h) | 100000 h |
| Rated life time L80/B50 at 25 °C | 65000 h |
| Lumen maintenance at median useful life of 35,000 hrs at 25 °C ambient (tq) (%) | 90 % |
| Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%) | 85 % |
| Lumen maintenance at median useful life of 100,000 hr at 25 °C ambient (tq) | 70 % |
| Failure rate at median useful life of 35,000 hrs at 25 °C ambient (tq) (%) | 5 % |
| Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%) | 5 % |
| Failure rate at median useful life of 100,000 hrs at 25 °C ambient (tq) | 10 % |
| Rated ambient temperature acc. IEC62722-2-1 (min) (°C) | 0 °C |
| Rated ambient temperature acc. IEC62722-2-1 (max) (°C) | 25 °C |

| Measurements | |
|---|---|
| Length (mm) | 80 mm |
| Width (mm) | 80 mm |
| Height/depth (mm) | 130 mm |
| Outer diameter (mm) | 80 mm |
| Installation height (min) (mm) | 3000 mm |
| Installation height (max) (mm) | 6000 mm |