# Blitz Sq M Double



## IP65 31W/830 16D GLC WH Sq

Outdoors wall luminaire


Blitz Sq M Double is a surface-mounted wall luminaire with a rectangular design, and it distributes light in two directions. The luminaire is suitable for indoor and outdoor use. Integrated LED. Available with three different beams. High-quality surface treatment, stainless steel screws.

Blitz Sq M Double Outdoors wall luminaire 31W 3000K 3180lm No dim; IP65; IK07; Protection cl. I; L70B50 50000h; LED not exchangeable; CRI>80; SDCM3; Ending; 3x2.5mm²; Housing al; Colour wh; Cover Glass transparent; C16 max. 35

Stocked: No

**IP65 31W/830 16D GLC WH Sq**

| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
|---|---|---|---|
| 4511619 | 4511619 | 3.1 | Blitz Sq M Double |



# IP65 31W/830 16D GLC WH Sq

EC002892 Ceiling / wall luminaire

| Mounting | |
|---|---|
| Suitable for wall mounting | Yes |
| Suitable for suspended mounting | No |
| Suitable for ceiling mounting | No |
| Suitable for recessed mounting | No |
| Suitable for surface mounting | Yes |
| Suitable for light line configuration | No |
| Suitable for clamp-mounting | No |
| Fit for workplace acc. EN 12464-1 | No |
| Degree of protection (IP) | IP65 |
| Degree of protection (IP), rear side | IP65 |
| Degree of protection (IP), front side | IP65 |
| Max. number of luminaires per miniature circuit breaker C10 (MCB) | 23 |
| Max. number of luminaires per miniature circuit breaker B16 | 23 |
| Max. number of luminaires per miniature circuit breaker C16 | 35 |
| Impact strength | IK07 |
| Luminaire with limited surface temperature, class "D“ in acc. with EN 60598-2-24 | No |
| Suitable for emergency lighting | No |
| Emergency function monitoring system | None |
| Type of wiring | Ending |
| Number of poles | 3 |
| Conductor cross section (mm²) | 2.5 mm² |
| Connection type | Screwed terminal |
| Connectable conductor cross section (min) (mm²) | 1.5 mm² |
| Connectable conductor cross section (max) (mm²) | 2.5 mm² |

| Structure | |
|---|---|
| With mounting material | Yes |
| Lamp type | LED not exchangeable |
| Light source included | Yes |
| Suitable for number of lamps | 2 |
| Lamp holder | Other |
| Housing material | Aluminium |
| Housing surface protection | Powder coating |
| Housing colour | White |
| Cover material | Glass transparent |
| Type of grid | None |
| Control gear included | Yes |
| Exchangeable control gear | Yes |
| Energy efficiency class of light source according to EU regulation 2019/2015 | C |
| Containing product according to 2019/2020/EU | Yes |
| Emergency power supply system | None |
| Emergency power supply integrated | No |
| With switch | No |
| With air slots | No |
| Filament test according to IEC 60695-2-11 | 650 °C - 30 s |

| Electrotechnical data | |
|---|---|
| Voltage type | AC |
| Nominal voltage (min) (V) | 220 V |
| Nominal voltage (max) (V) | 240 V |
| Nominal current (min) (mA) | 530 mA |
| Nominal current (max) (mA) | 530 mA |
| Type of control gear | LED operating device current-controlled |
| Protection class according to IEC 61140 | I |
| Suitable for lamp power (min) (W) | 31 W |
| Suitable for lamp power (max) (W) | 31 W |
| Luminaire efficacy (min) (lm/W) | 102 lm/W |
| Luminaire efficacy (max) (lm/W) | 102 lm/W |
| Maximum system power (W) | 31 W |
| Luminaire efficacy (lm/W) | 102 lm/W |
| Power factor | 0.9 |
| Total harmonic distortion (THD) (%) | 20 % |
| Total harmonic distortion | 20 THD |

| Dimming and control | |
|---|---|
| Dimmable | No |
| Dimming 0-10 V | No |
| Dimming 1-10 V | No |
| Dimming DALI | No |
| Dimming DALI-2 | No |
| Dimming DMX | No |
| Dimming DSI | No |
| Dimming LineSwitch | No |
| Dimming manufacturer's proprietary system | No |
| Dimming mains voltage modulation | No |
| Dimming trailing edge | No |
| Dimming leading edge | No |
| Dimming programmable | No |
| Dimming potentiometer (integrated) | No |
| Dimming RF | No |
| Dimming Sine Wave Reduction | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming with push-button | No |
| No dimming function | Yes |
| With presence indicator | No |
| With movement sensor | No |
| With light sensor | No |
| Constant luminous flux control | No |
| Bluetooth operated | No |
| Compatible with Casambi | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

| Photometric data | |
|---|---|
| Light distributor | Reflector |
| Light sharing | Symmetric |
| Beam angle | Narrow beam 10-20° |
| Colour consistency (McAdam ellipse) | SDCM3 |
| Light outlet | Direct/indirect |
| Rated luminous flux according to IEC 62722-2- 1 (min) (lm) | 3180 lm |
| Rated luminous flux according to IEC 62722-2- 1 (max) (lm) | 3180 lm |
| Colour of light (alphanumeric) | White |
| Effective luminous flux (lm) | 3180 lm |
| Colour temperature (min) (K) | 3000 K |
| Colour temperature (max) (K) | 3000 K |
| Flickering value Pst LM | 1 |
| Colour rendering index (CRI/Ra) | 80-89 |
| Stroboscope effect value SVM | 0.4 |
| Photobiological safety according to EN 62471 | RG0 |
| Colour temperature switchable | No |
| Lumen setting adjustable | No |
| Beam angle adjustable | No |

| Lifetime and capacity | |
|---|---|
| Rated life time L70/B50 at 25 °C (h) | 50000 h |
| Rated life time L80/B50 at 25 °C | 35000 h |
| Lumen maintenance at median useful life of 35,000 hrs at 25 °C ambient (tq) (%) | 80 % |
| Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%) | 70 % |
| Failure rate at median useful life of 35,000 hrs at 25 °C ambient (tq) (%) | 5 % |
| Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%) | 10 % |
| Rated ambient temperature acc. IEC62722-2-1 (min) (°C) | -25 °C |
| Rated ambient temperature acc. IEC62722-2-1 (max) (°C) | 25 °C |

| Measurements | |
|---|---|
| Width (mm) | 130 mm |
| Height/depth (mm) | 220 mm |
| Length (mm) | 130 mm |
| Outer diameter (mm) | 130 mm |