# Park

## IP44 E27 PCC RST

Outdoors wall luminaire

The clean-lined and stylish Park garden luminaires blend in with modern residential architecture. The steel rings inside the diffuser prevent glare and bring the modern design to life. Combine these models with Park Bollard luminaires to create a harmonious and stylish lighting solution for your outdoor spaces. You can change the atmosphere and level of illumination through the choice of lamp.

Park Outdoors wall luminaire No dim; IP44; Protection cl. I; LED exchangeable; Ending; 3x2.5mm²; Housing st; Colour st; Cover Plastic, transparent

Stocked: Yes






| IP44 E27 PCC RST | | | |
|---|---|---|---|
| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
| 4546530 | 4546530 | 0.94 | Park |

# IP44 E27 PCC RST

EC002892 Ceiling / wall luminaire

| Mounting | |
|---|---|
| Suitable for wall mounting | Yes |
| Suitable for suspended mounting | No |
| Suitable for ceiling mounting | No |
| Suitable for recessed mounting | No |
| Suitable for surface mounting | Yes |
| Suitable for light line configuration | No |
| Suitable for clamp-mounting | No |
| Fit for workplace acc. EN 12464-1 | No |
| Degree of protection (IP) | IP44 |
| Degree of protection (IP), rear side | IP44 |
| Degree of protection (IP), front side | IP44 |
| Luminaire with limited surface temperature, class "D“ in acc. with EN 60598-2-24 | No |
| Suitable for emergency lighting | No |
| Type of wiring | Ending |
| Number of poles | 3 |
| Conductor cross section (mm²) | 2.5 mm² |
| Connection type | Screwed terminal |

| Structure | |
|---|---|
| With mounting material | Yes |
| Lamp type | LED exchangeable |
| Light source included | No |
| Suitable for number of lamps | 1 |
| Lamp holder | E27 |
| Housing material | Stainless steel |
| Housing surface protection | Untreated |
| Housing colour | Stainless steel |
| Cover material | Plastic, transparent |
| Type of grid | Other |
| Control gear included | No |
| Energy efficiency class of light source according to EU regulation 2019/2015 | Not required |
| Emergency power supply integrated | No |
| With switch | No |
| With air slots | No |
| Filament test according to IEC 60695-2-11 | 650 °C - 30 s |

| Electrotechnical data | |
|---|---|
| Voltage type | AC |
| Nominal voltage (min) (V) | 230 V |
| Nominal voltage (max) (V) | 230 V |
| Type of control gear | Not required |
| Protection class according to IEC 61140 | I |
| Suitable for lamp power (min) (W) | 1 W |
| Suitable for lamp power (max) (W) | 10.5 W |

| Dimming and control | |
|---|---|
| Dimming 0-10 V | No |
| Dimming 1-10 V | No |
| Dimming DALI | No |
| Dimming DALI-2 | No |
| Dimming DMX | No |
| Dimming DSI | No |
| Dimming LineSwitch | No |
| Dimming manufacturer's proprietary system | No |
| Dimming mains voltage modulation | No |
| Dimming trailing edge | No |
| Dimming leading edge | No |
| Dimming programmable | No |
| Dimming potentiometer (integrated) | No |
| Dimming RF | No |
| Dimming Sine Wave Reduction | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming with push-button | No |
| No dimming function | Yes |
| With movement sensor | No |
| With light sensor | No |
| Constant luminous flux control | No |
| Bluetooth operated | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

| Photometric data | |
|---|---|
| Light distributor | Reflector |
| Light sharing | Symmetric |
| Light outlet | Direct |
| Colour temperature switchable | No |
| Lumen setting adjustable | No |
| Beam angle adjustable | No |

| Lifetime and capacity | |
|---|---|
| Rated ambient temperature acc. IEC62722-2-1 (min) (°C) | -20 °C |
| Rated ambient temperature acc. IEC62722-2-1 (max) (°C) | 25 °C |

| Measurements | |
|---|---|
| Width (mm) | 115 mm |
| Height/depth (mm) | 280 mm |
| Length (mm) | 150 mm |
| Outer diameter (mm) | 100 mm |