# Onni



LED lamp

A highly comprehensive lamp range offering solutions for all home lighting needs. Lightweight and durable lamps that fully replace incandescent, halogen and energy-saving lamps. The colour temperature is a pleasant warm white (2700 K). The opal light source provides uniform, glare-free illumination. Technical specifications are clearly presented on the packaging.

Stocked: Yes

| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
|---|---|---|---|
| 4710242 | 4710242 | 0.032 | Onni |

EC001959 LED Lamp

| Electrotechnical data | |
|---|---|
| Nominal voltage (min) (V) | 220 V |
| Nominal voltage (max) (V) | 240 V |
| Power factor | 0.5 |
| Lamp power (min) (W) | 7 W |
| Lamp power (max) (W) | 7 W |
| Voltage type | AC |

| ETIM | |
|---|---|
| Suitable for electronic ballast | No |
| Suitable for magnetic ballast | No |
| Rated luminous flux according to IEC 62612 (lm) | 806 lm |
| Lamp efficacy (lm/W) | 115 lm/W |
| Lamp shape | Round/globe |
| Filament lamp | No |
| Type of glass/cover | Opal |
| Cap | E27 |
| Energy efficiency class according to EU regulation 2019/2015 | E |
| Lamp designation | A-type |
| Min. number of switching cycles | 50000 |
| Weighted energy consumption in 1,000 hours (kWh) | 7 kWh |
| Average nominal lifespan (h) | 15000 h |

| Photometric data | |
|---|---|
| Luminous flux (min) (lm) | 806 lm |
| Luminous flux (max) (lm) | 806 lm |
| Colour rendering index (CRI/Ra) | 80-89 |
| Colour of light acc. EN 12464-1 | Warm <3300 K |
| Colour temperature (min) (K) | 2700 K |
| Colour temperature (max) (K) | 2700 K |
| Beam angle (min) (°) | 360 ° |
| Beam angle (max) (°) | 360 ° |
| Colour consistency (McAdam ellipse) | SDCM6 |

| Structure | |
|---|---|
| Material of light bulb | Glass |
| Colour | White |
| Housing colour | White |

| Dimming and control | |
|---|---|
| Dimmable | Yes |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming Bluetooth | No |
| Dimming Wi-Fi | No |
| No dimming function | No |
| Remote operation possible | No |
| With movement sensor | No |
| With remote control | No |
| With twilight switch | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

| Measurements | |
|---|---|
| Diameter (mm) | 60 mm |
| Length (mm) | 108 mm |

| Mounting | |
|---|---|
| Degree of protection (IP) | IP20 |