Plant



LED lamp

In the dark Nordic winter, houseplants need additional light from November to March. Grow lights are designed to meet the specific light requirements of plants, with red and blue wavelengths being the most important for growth. By enhancing these wavelengths, plants grow stronger and develop better height. Grow lights are not intended for general room lighting, as some models in the range emit a strongly reddish light. Technical specifications and light colour are clearly indicated on the packaging.

Clear classic filament LED plant lamp 5W E27 160lm 10 000h 60x105mm, cardboard packing. Supply frequency ~50/60Hz.

Stocked: Yes

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4713402	4713402	0.032	Plant

EC001959 LED Lamp

Electrotechnical data	
Nominal voltage (min) (V)	220 V
Nominal voltage (max) (V)	240 V
Nominal current (min) (mA)	47 mA
Nominal current (max) (mA)	47 mA
Power factor	0.5
Lamp power (min) (W)	5 W
Lamp power (max) (W)	5 W
Voltage type	AC

ETIM	
Suitable for electronic ballast	No
Suitable for magnetic ballast	No
Rated luminous flux according to IEC 62612 (lm)	160 lm
Lamp efficacy (lm/W)	36 lm/W
Lamp shape	Round/globe
Filament lamp	No
Type of glass/cover	Clear
Cap	E27
Lamp designation	A-type
Min. number of switching cycles	50000
Weighted energy consumption in 1,000 hours (kWh)	5 kWh
Average nominal lifespan (h)	10000 h

Photometric data	
Luminous flux (min) (lm)	160 lm
Luminous flux (max) (lm)	160 lm
Beam angle (min) (°)	320 °
Beam angle (max) (°)	320 °
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1

Structure	
Material of light bulb	Glass
Colour	Other
Housing colour	Colourless

Dimming and control	
Dimmable	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	Yes
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Measurements	
Diameter (mm)	60 mm
Length (mm)	105 mm

Mounting	
Degree of protection (IP)	IP20