

Frost



LED lamp

The lamps in the Frost range are specifically designed for cold environments. The LED frost lamp maintains reliable operation all year round. The operating temperature range is exceptionally wide, from –40 °C to +40 °C. Technical specifications are clearly presented on the packaging. Standard bulb models (A60) are available in warm white 2800 K or cool white 4000 K. The cylindrical Tubular lamps (TUB37) are ideal for slim outdoor luminaires. Tubular lamps emit white light at 3000 K or cool white light at 4000 K.

Opal tubular LED lamp for cold environments, -40 °C, 9.5 W, 3000 K, E27, 1055 lm, 15,000 h, 45×152 mm, cardboard packaging. Frequency ~50/60 Hz.

Stocked: Yes

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4714168	4714168	0.076	Frost

AIRAM

EC001959 LED Lamp

Electrotechnical data	
Nominal voltage (min) (V)	220 V
Nominal voltage (max) (V)	240 V
Nominal current (min) (mA)	54 mA
Nominal current (max) (mA)	54 mA
Power factor	0.5
Lamp power (min) (W)	9.5 W
Lamp power (max) (W)	9.5 W
Voltage type	AC

ETIM	
Suitable for electronic ballast	No
Suitable for magnetic ballast	No
Rated luminous flux according to IEC 62612 (lm)	1055 lm
Lamp efficacy (lm/W)	111 lm/W
Lamp shape	Other
Filament lamp	No
Type of glass/cover	Opal
Cap	E27
Energy efficiency class according to EU regulation 2019/2015	E
Lamp designation	Other
Min. number of switching cycles	50000
Weighted energy consumption in 1,000 hours (kWh)	10 kWh
Average nominal lifespan (h)	15000 h

Photometric data	
Luminous flux (min) (lm)	1055 lm
Luminous flux (max) (lm)	1055 lm
Colour rendering index (CRI/Ra)	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	3000 K
Colour temperature (max) (K)	3000 K
Beam angle (min) (°)	270 °
Beam angle (max) (°)	270 °
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1

Structure	
Material of light bulb	Plastic
Colour	White
Housing colour	White

Dimming and control	
Dimmable	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	Yes
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Measurements	
Diameter (mm)	45 mm
Length (mm)	152 mm

Mounting	
Degree of protection (IP)	IP20

AIRAM