3-step dim



Reflector lamp

Use the 3-Step-DIM bulbs to easily change the atmosphere of your home. You can gradually adjust the light level of the bulbs with just a regular light switch! You do not need a separate dimmer. When you press the light switch for the first time, the bulb’s light output is 100%. You can dim the lamp by pressing the light switch again within three seconds. Memory function: when you switch off the bulb completely, it retains the last dimmer setting. The bulbs have a beautiful opal glass globe. The color temperature of the light is a cool white 4000 K.

Stocked: Yes

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4714175	4714175	0.04	3-step dim

EC001959 LED Lamp

Electrotechnical data	
Nominal voltage (min) (V)	220 V
Nominal voltage (max) (V)	240 V
Nominal current (min) (mA)	40 mA
Nominal current (max) (mA)	40 mA
Power factor	0.5
Lamp power (min) (W)	5 W
Lamp power (max) (W)	5 W
Voltage type	AC

ETIM	
Suitable for electronic ballast	No
Suitable for magnetic ballast	No
Rated luminous flux according to IEC 62612 (lm)	390 lm
Lamp efficacy (lm/W)	78 lm/W
Lamp shape	Reflector
Filament lamp	No
Type of glass/cover	Other
Cap	GU10
Energy efficiency class according to EU regulation 2019/2015	F
Lamp designation	PAR16
Min. number of switching cycles	50000
Weighted energy consumption in 1,000 hours (kWh)	5 kWh
Average nominal lifespan (h)	15000 h

Photometric data	
Luminous flux (min) (lm)	390 lm
Luminous flux (max) (lm)	390 lm
Luminous intensity (cd)	600 cd
Colour rendering index (CRI/Ra)	80-89
Colour of light acc. EN 12464-1	Neutral 3300-5300 K
Colour temperature (min) (K)	4000 K
Colour temperature (max) (K)	4000 K
Beam angle (min) (°)	36 °
Beam angle (max) (°)	36 °
Colour consistency (McAdam ellipse)	SDCM6

Structure	
Material of light bulb	Glass
Colour	Other
Housing colour	Grey

Dimming and control	
Dimmable	Yes
Dimming trailing edge	No
Dimming leading edge	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	No
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Measurements	
Diameter (mm)	50 mm
Length (mm)	53 mm

Mounting	
Degree of protection (IP)	IP20