# Pro Dim



LED lamp

The selection of Airam Pro LED 3000 K full glass filament bulbs is highly versatile. The range includes several different lumen options. All models are dimmable. The bulb provides a fully comprehensive 360-degree light distribution, meaning it also emits light toward the base. The opal cover ensures glare-free illumination.

Opal classic dimmable LED lamp 11W 3000K E27 1521lm 25000h 60x108mm, cardboard packing. Supply frequency ~50/60Hz.

Stocked: Yes

| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
|---|---|---|---|
| 4714176 | 4714176 | 0.032 | Pro Dim |

EC001959 LED Lamp

| Electrotechnical data | |
|---|---|
| Nominal voltage (min) (V) | 220 V |
| Nominal voltage (max) (V) | 240 V |
| Power factor | 0.7 |
| Lamp power (min) (W) | 11 W |
| Lamp power (max) (W) | 11 W |
| Voltage type | AC |

| ETIM | |
|---|---|
| Suitable for electronic ballast | No |
| Suitable for magnetic ballast | No |
| Rated luminous flux according to IEC 62612 (lm) | 1521 lm |
| Lamp efficacy (lm/W) | 138 lm/W |
| Lamp shape | Round/globe |
| Filament lamp | No |
| Type of glass/cover | Opal |
| Cap | E27 |
| Energy efficiency class according to EU regulation 2019/2015 | D |
| Lamp designation | A-type |
| Min. number of switching cycles | 500000 |
| Weighted energy consumption in 1,000 hours (kWh) | 11 kWh |
| Average nominal lifespan (h) | 25000 h |

| Photometric data | |
|---|---|
| Luminous flux (min) (lm) | 1521 lm |
| Luminous flux (max) (lm) | 1521 lm |
| Colour rendering index (CRI/Ra) | 80-89 |
| Colour of light acc. EN 12464-1 | Warm <3300 K |
| Colour temperature (min) (K) | 3000 K |
| Colour temperature (max) (K) | 3000 K |
| Beam angle (min) (°) | 360 ° |
| Beam angle (max) (°) | 360 ° |
| Colour consistency (McAdam ellipse) | SDCM6 |
| Photobiological safety according to EN 62471 | RG1 |

| Structure | |
|---|---|
| Colour | White |
| Housing colour | White |

| Dimming and control | |
|---|---|
| Dimmable | Yes |
| Dimming trailing edge | Yes |
| Dimming leading edge | Yes |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming Bluetooth | No |
| Dimming Wi-Fi | No |
| No dimming function | No |
| Remote operation possible | No |
| With movement sensor | No |
| With remote control | No |
| With twilight switch | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

| Measurements | |
|---|---|
| Diameter (mm) | 60 mm |
| Length (mm) | 108 mm |

| Mounting | |
|---|---|
| Degree of protection (IP) | IP20 |