# Office P




## 1545 58W/840 CA AL MA WH P

Suspension luminaire

The suspension-mounted Office P is an energy-efficient office luminaire range with a downlight. This extensive range offers numerous customisation options. Its optics features include an aluminium parabolic louvre and integrated opal shield, which eliminate glare from the LEDs and achieve a low Unified Glare Rating l/value (UGR <19). The luminaire is delivered with a 2-metre cable. Typical applications include schools, offices and other spaces where computers are used.

Office P Suspension luminaire 58W 4000K 7000lm Dim programmable; IP20; IK02; Protection cl. I; L80B10 100000h; LED not exchangeable; Lamp included; CRI>80; SDCM3; Ending; 3x1mm²; Housing Steel; Colour wh; Cover Plastic matt/satinized




Stocked: No

| 1545 58W/840 CA AL MA WH P | | | |
|---|---|---|---|
| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
| | A1OFBH-CA | 3 | Office P |

# 1545 58W/840 CA AL MA WH P

EC001743 Pendant luminaire

| Mounting | |
|---|---|
| Suitable for light line configuration | No |
| Fit for workplace acc. EN 12464-1 | Yes |
| Degree of protection (IP) | IP20 |
| Impact strength | IK02 |
| Luminaire with limited surface temperature, class "D“ in acc. with EN 60598-2-24 | Yes |
| Suitable for emergency lighting | No |
| Emergency function monitoring system | None |
| Type of wiring | Ending |
| Connectable conductor cross section (min) (mm²) | 1.5 mm² |
| Connectable conductor cross section (max) (mm²) | 2.5 mm² |
| Number of poles | 3 |
| Conductor cross section (mm²) | 1 mm² |
| Connection type | Other |

| Structure | |
|---|---|
| Lamp type | LED not exchangeable |
| Light source included | Yes |
| Suitable for number of lamps | 1 |
| Lamp holder | Other |
| Housing material | Steel |
| Housing colour | White |
| Cover material | Plastic matt/satinized |
| Type of grid | Matt |
| Control gear included | Yes |
| Exchangeable control gear | Yes |
| Reflector | Matt |
| Energy efficiency class of light source according to EU regulation 2019/2015 | D |
| Containing product according to 2019/2020/EU | Yes |
| Emergency power supply integrated | No |
| Emergency power supply system | None |
| Filament test according to IEC 60695-2-11 | 650 °C - 30 s |
| Suspension supplied with the product | No |
| Pendant length (min) (mm) | 500 mm |
| Pendant length (max) (mm) | 2000 mm |

| Electrotechnical data | |
|---|---|
| Voltage type | AC |
| Nominal voltage (min) (V) | 220 V |
| Nominal voltage (max) (V) | 240 V |
| Nominal current (min) (mA) | 700 mA |
| Nominal current (max) (mA) | 700 mA |
| Type of control gear | LED operating device current-controlled |
| Protection class according to IEC 61140 | I |
| Luminaire efficacy (min) (lm/W) | 120 lm/W |
| Luminaire efficacy (max) (lm/W) | 120 lm/W |
| Suitable for lamp power (min) (W) | 58 W |
| Suitable for lamp power (max) (W) | 58 W |
| Maximum system power (W) | 58 W |
| Luminaire efficacy (lm/W) | 120 lm/W |
| Power factor | 0.9 |

| Dimming and control | |
|---|---|
| Dimmable | Yes |
| Dimming 0-10 V | No |
| Dimming 1-10 V | No |
| Dimming DALI | No |
| Dimming DALI-2 | No |
| Dimming DMX | No |
| Dimming DSI | No |
| Dimming manufacturer's proprietary system | No |
| Dimming mains voltage modulation | No |
| Dimming trailing edge | No |
| Dimming leading edge | No |
| Dimming potentiometer (integrated) | No |
| Dimming programmable | Yes |
| Dimming RF | No |
| Dimming LineSwitch | No |
| Dimming Sine Wave Reduction | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming with push-button | No |
| No dimming function | No |
| With movement sensor | No |
| With presence indicator | No |
| With light sensor | No |
| Constant luminous flux control | Yes |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| Compatible with Casambi | Yes |
| IFTTT support available | No |
| Bluetooth operated | Yes |

| Photometric data | |
|---|---|
| Light distributor | Reflector |
| Light sharing | Symmetric |
| Colour consistency (McAdam ellipse) | SDCM3 |
| Light outlet | Direct |
| Direct-/indirect proportion separately controllabl | No |
| Rated luminous flux according to IEC 62722-2- 1 (min) (lm) | 7000 lm |
| Rated luminous flux according to IEC 62722-2- 1 (max) (lm) | 7000 lm |
| Effective luminous flux (lm) | 7000 lm |
| Colour of light (alphanumeric) | White |
| Colour temperature (min) (K) | 4000 K |
| Colour temperature (max) (K) | 4000 K |
| Colour rendering index (CRI/Ra) | 80-89 |
| Unified Glare Rating (UGR) | 19 |
| Flickering value Pst LM | 1 |
| Stroboscope effect value SVM | 0.4 |
| Colour temperature switchable | No |
| Lumen setting adjustable | No |
| Beam angle adjustable | No |

| Lifetime and capacity | |
|---|---|
| Rated life time L70/B50 at 25 °C (h) | 100000 h |
| Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%) | 90 % |
| Lumen maintenance at median useful life of 75,000 hrs at 25 °C ambient (tq) (%) | 85 % |
| Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%) | 5 % |
| Failure rate at median useful life of 75,000 hrs at 25 °C ambient (tq) (%) | 10 % |

| Measurements | |
|---|---|
| Width (mm) | 140 mm |
| Height/depth (mm) | 60 mm |
| Length (mm) | 1545 mm |