Target M


IP20 21W/930 2580lm 36D DA2 WH



Spotlight

Target M offers an ideal spotlight solution for retail premises. This luminaire offers high-quality illumination and excellent colour rendering properties. Its Premium White feature is specifically designed for in-store spot and accent lighting. The feature enhances colour contrasts, emphasising white colour tones. The luminaire is equipped with an almost inconspicuous ballast that is integrated into a three-phase rail. Thanks to its versatility, this luminaire offers a wide range of lighting options for retail spaces as it is easy to move and adjust. Suitable applications include fashion and clothing retail premises, museums and other public spaces.

Target M Spotlight 21W 3000K 2580lm Beam angle Medium beam 20-40°; Dim programmable; IP20; IK02; Protection cl. II; L70B50 100000h; LED not exchangeable; Lamp included; CRI>90; SDCM3; Ending; 5x2.5mm²; Housing al; Colour wh; Cover Plastic, transparent; C16 max. 61



Stocked: No

IP20 21W/930 2580lm 36D DA2 WH			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
	A1TATB-DALI	0.7	Target M

IP20 21W/930 2580lm 36D DA2 WH

EC001744 Downlight / spot luminaire / floodlight

Mounting	
Suitable for surface mounting	No
Suitable for recessed mounting	No
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	Yes
Suitable for traverse mounting	No
Suitable for pedestal/floor mounting	No
Suitable for light-track mounting	Yes
Suitable for clamp-mounting	No
Suitable for low voltage cable system	No
Degree of protection (IP)	IP20
Degree of protection (IP), rear side	IP20
Degree of protection (IP), front side	IP20
Impact strength	IK02
Emergency function monitoring system	None
Type of wiring	Ending
Number of poles	5
Conductor cross section (mm²)	2.5 mm²
Connectable conductor cross section (min) (mm²)	1.5 mm²
Connectable conductor cross section (max) (mm²)	2.5 mm²
Connection type	Busbar adapter
Luminaire with limited surface temperature, class "D“ in acc. with EN 60598-2-24	No
Max. number of luminaires per miniature circuit breaker B16	50
Max. number of luminaires per miniature circuit breaker C16	85
Fit for workplace acc. EN 12464-1	No
Luminaire may be covered with thermally insulating material	-

Structure	
Adjustability	Rotating and swivelling
Lamp type	LED not exchangeable
Light source included	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Aluminium
Surface protection	Powder coating
Housing colour	White
Cover material	Plastic, transparent
Surface brushed	No
Control gear included	Yes
Exchangeable control gear	Yes
Reflector	High-gloss
Reflector colour	Silver
Energy efficiency class of light source according to EU regulation 2019/2015	E
Containing product according to 2019/2020/EU	Yes
Emergency power supply system	None
Emergency power supply integrated	No
Filament test according to IEC 60695-2-11	650 °C - 30 s

AIRAM

Dimming and control	
With movement sensor	No
With presence indicator	No
With light sensor	No
Dimmable	Yes
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI-2	Yes
Dimming DALI	No
Dimming DMX	No
Dimming DSI	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	Yes
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	No
Constant luminous flux control	No
IFTTT support available	No
Compatible with Apple HomeKit	No
Bluetooth operated	No
Compatible with Google Assistant	No
Compatible with Casambi	No
Compatible with Amazon Alexa	No

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220 V
Nominal voltage (max) (V)	240 V
Nominal current (min) (mA)	550 mA
Nominal current (max) (mA)	550 mA
Type of control gear	LED operating device current-controlled
Total harmonic distortion (THD) (%)	15 %
Total harmonic distortion	15 THD
Protection class according to IEC 61140	II
Suitable for lamp power (min) (W)	21 W
Suitable for lamp power (max) (W)	21 W
Maximum system power (W)	21 W
Luminaire efficacy (min) (lm/W)	123 lm/W
Luminaire efficacy (max) (lm/W)	123 lm/W
Power factor	0.95
Luminaire efficacy (lm/W)	123 lm/W

Photometric data	
Light distributor	Reflector
Light sharing	Symmetric
Beam angle	Medium beam 20-40°
Light outlet	Direct
Colour of light (alphanumeric)	White
Colour temperature (min) (K)	3000 K
Colour temperature (max) (K)	3000 K
Colour temperature switchable	No
Colour rendering index (CRI/Ra)	90-100
Luminous flux (min) (lm)	2580 lm
Luminous flux (max) (lm)	2580 lm
Effective luminous flux (lm)	2580 lm
Rated luminous flux according to IEC 62722-2- 1 (min) (lm)	2580 lm
Rated luminous flux according to IEC 62722-2- 1 (max) (lm)	2580 lm
Lumen setting adjustable	Continuously variable
Flickering value Pst LM	1
Beam angle adjustable	No
Stroboscope effect value SVM	0.4
Photobiological safety according to EN 62471	RG1
Colour consistency (McAdam ellipse)	SDCM3

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	100000 h
Rated life time L80/B50 at 25 °C	65000 h
Lumen maintenance at median useful life of 35,000 hrs at 25 °C ambient (tq) (%)	90 %
Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	85 %
Lumen maintenance at median useful life of 100,000 hr at 25 °C ambient (tq)	70 %
Failure rate at median useful life of 35,000 hrs at 25 °C ambient (tq) (%)	5 %
Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	5 %
Failure rate at median useful life of 100,000 hrs at 25 °C ambient (tq)	10 %
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	0 °C
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	25 °C

Measurements	
Length (mm)	80 mm
Width (mm)	80 mm
Height/depth (mm)	130 mm
Outer diameter (mm)	80 mm
Installation height (min) (mm)	3000 mm
Installation height (max) (mm)	6000 mm