IP20 | 5 x 2,5 | DALI | DALI-2 | 5 year guarantee | STUL-TAKUU

Profi L


1510x238 IP20 41W/840 DA AL MA WH



Surface mnt./suspen. luminaire

A luminaire range designed for offices and other public spaces. Available in two housing lengths and widths. The range includes two colour temperatures and several output options. You can choose from models with one or two matte anti-glare shields. Suspension or surface mounting.

Profi L Surface mnt./suspen. luminaire 41W 4000K 5350lm Dim DALI-2; IP20; Protection cl. I; L70B50 100000h; LED not exchangeable; CRI>80; SDCM3; Suitable for through wiring; 5x2.5mm²; Housing Steel; Colour wh; Cover Other; C16 max. 26



Stocked: No

1510x238 IP20 41W/840 DA AL MA WH			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
	D2PREB-DALI	4.5	Profi L

AIRAM

1510x238 IP20 41W/840 DA AL MA WH

EC001743 Pendant luminaire

Mounting	
Suitable for light line configuration	No
Fit for workplace acc. EN 12464-1	Yes
Max. number of luminaires per miniature circuit breaker B16	24
Max. number of luminaires per miniature circuit breaker C16	40
Degree of protection (IP)	IP20
Impact strength	IK02
Luminaire with limited surface temperature, class "D“ in acc. with EN 60598-2-24	No
Suitable for emergency lighting	No
Emergency function monitoring system	None
Type of wiring	Suitable for through wiring
Connectable conductor cross section (min) (mm²)	1.5 mm²
Connectable conductor cross section (max) (mm²)	2.5 mm²
Number of poles	5
Conductor cross section (mm²)	2.5 mm²
Connection type	Screwless terminal

Structure	
Lamp type	LED not exchangeable
Light source included	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Steel
Housing colour	White
Cover material	Other
Type of grid	Matt
Control gear included	Yes
Reflector	Matt
Energy efficiency class of light source according to EU regulation 2019/2015	C
Containing product according to 2019/2020/EU	Yes
Emergency power supply integrated	No
Emergency power supply system	None
Filament test according to IEC 60695-2-11	650 °C - 30 s
Suspension supplied with the product	No

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220 V
Nominal voltage (max) (V)	240 V
Nominal current (min) (mA)	250 mA
Nominal current (max) (mA)	250 mA
Type of control gear	LED operating device current-controlled
Protection class according to IEC 61140	I
Luminaire efficacy (min) (lm/W)	130 lm/W
Luminaire efficacy (max) (lm/W)	130 lm/W
Suitable for lamp power (min) (W)	41 W
Suitable for lamp power (max) (W)	41 W
Maximum system power (W)	41 W
Luminaire efficacy (lm/W)	130 lm/W
Power factor	0.9

AIRAM

Dimming and control	
Dimmable	Yes
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	Yes
Dimming DALI-2	Yes
Dimming DMX	No
Dimming DSI	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming potentiometer (integrated)	No
Dimming programmable	No
Dimming RF	No
Dimming LineSwitch	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	No
With movement sensor	No
With presence indicator	No
With light sensor	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
Compatible with Casambi	No
IFTTT support available	No
Bluetooth operated	No

Photometric data	
Light distributor	Reflector
Light sharing	Symmetric
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Rated luminous flux according to IEC 62722-2- 1 (min) (lm)	5350 lm
Rated luminous flux according to IEC 62722-2- 1 (max) (lm)	5350 lm
Effective luminous flux (lm)	5350 lm
Colour of light (alphanumeric)	White
Colour temperature (min) (K)	4000 K
Colour temperature (max) (K)	4000 K
Colour rendering index (CRI/Ra)	80-89
Unified Glare Rating (UGR)	19
Flickering value Pst LM	1
Stroboscope effect value SVM	0.4
Colour temperature switchable	No

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	100000 h

Measurements	
Width (mm)	238 mm
Height/depth (mm)	52 mm
Length (mm)	1510 mm